

# FINAL REVIEW PART 1 (PRE-MT2)

---

COMPUTER SCIENCE MENTORS

April 19, 2021 - April 21, 2021

---

## 1 Environment Diagrams


---

1. Draw the environment diagram that results from running the following code.

```
def f(f):  
    def h(x, y):  
        z = 4  
        return lambda z: (x + y) * z  
  
    def g(y):  
        nonlocal g, h  
        g = lambda y: y[:4]  
        h = lambda x, y: lambda f: f(x + y)  
        return y[3] + y[5:8]  
  
    return h(g("sarcasm!"), g("why?"))  
  
f = f("61a")(2)
```

2. Fill in each blank in the code example below so that its environment diagram is the following. You do not need to use all the blanks.

```
fruit = [1, 2, [3, 4]]
fruit._____
fruit[3][2]._____
fruit[2][2]._____
fruit[3][3][2][2][2][1] = _____
```



**2 OOP**

1. The `DLList` class is a spin off of the normal `Link` class we learned in class; each `DLList` link has a `prev` attribute that keeps track of the previous link and a `next` attribute that keeps track of the next link. Fill in the following methods for the `DLList` class.

```
(a) class DLList:
    """
    >>> lst = DLList(6, DLList(1))
    >>> lst.value
    6
    >>> lst.next.value
    1
    >>> lst.prev.value
    AttributeError: 'NoneType' object has no attribute 'value'
    """
    empty = None
    def __init__(self, value, next=empty, prev=empty):
        _____
        _____
        _____
```

```
(b) def add_last(self, value):
    """
    >>> lst = DLList(6)
    >>> lst.add_last(1)
    >>> lst.value
    6
    >>> lst.next.value
    1
    >>> lst.next.prev.value
    6
    """
    pointer = self
    while _____:
        _____
```

```

    _____ = DLList(_____)
(c) def add_first(self, value):
    """
    >>> lst = DLList('A')
    >>> lst.add_first(1)
    >>> lst.value
    1
    >>> lst.next.value
    'A'
    >>> lst.next.prev.value
    1
    >>> lst.add_first(6)
    >>> lst.value
    6
    >>> lst.next.next.prev.value
    1
    """
    old_first = DLList(_____)

    _____ = _____

    _____ = _____

if _____:

    _____

```

---

### 3 Complexity

---

1. **Fast Exponentiation:** in this problem, we will examine a real-world algorithm used to improve the speed of calculating exponents.

(a) First, express the runtime of the naive exponentiation algorithm in big- $\theta$  notation.

```
def exp(b, n):
    if n == 0:
        return 1
    else:
        return b * exp(b, n - 1)
```

(b) Now, express the runtime of the fast exponentiation algorithm in big- $\theta$  notation.

```
def fast_exp(b, n):
    if n == 0:
        return 1
    elif n % 2 == 0: # Assume square runs in constant time
        return square(fast_exp(b, n // 2))
    else:
        return b * fast_exp(b, n - 1)
```


(c) What about this slightly modified version of fast\_exp?

```
def fast_exp(b, n):
    for _ in range(50 * n):
        print("Killing time")
    if n == 0:
        return 1
    elif n % 2 == 0:
        return square(fast_exp(b, n // 2))
    else:
        return b * fast_exp(b, n - 1)
```

## 4 Trees

1. Implement `rotate`, which takes in a tree and rotates the labels at each level of the tree by one to the left destructively. This rotation should be modular (That is, the leftmost label at a level will become the rightmost label after running `rotate`). You do NOT need to rotate across different branches.

For example, given tree `t` on the left, `rotate(t)` should mutate `t` to give us the right.



```

def rotate(t):
    """
    >>> t1 = Tree(1, [Tree(2), Tree(3, [Tree(4)]), Tree(5)])
    >>> rotate(t1)
    >>> t1
    Tree(1, [Tree(3), Tree(5, [Tree(4)]), Tree(2)])
    >>> t2 = Tree(1, [Tree(2, [Tree(3), Tree(4)]),
                    Tree(5, [Tree(6)])])
    >>> rotate(t2)
    >>> t2
    Tree(1, [Tree(5, [Tree(4), Tree(3)]),
            Tree(2, [Tree(6)])])
    """
    branch_labels = _____
  
```

```

n = len(t.branches)
  
```

```

for _____:
  
```

```

    _____
    _____
    _____
  
```

## 5 Generators

1. (a) Implement `n_apply`, which takes in 3 inputs `f`, `n`, `x`, and outputs the result of applying `f`, a function, `n` times to `x`. For example, for `n = 3`, output the result of `f(f(f(x)))`.

```
def n_apply(f, n, x):
    """
    >>> n_apply(lambda x: x + 1, 3, 2)
    5
    """

    for _____:

        x = _____

    return _____
```

- (b) Now implement `list_gen`, which takes in some list of integers `lst` and a function `f`. For the element at index `i` of `lst`, `list_gen` should apply `f` to the element `i` times and yield this value `lst[i]` times. You may use `n_apply` from the previous part.

```
def list_gen(lst, f):
    """
    >>> a = list_gen([1, 2, 3], lambda x: x + 1)
    >>> list(a)
    [1, 3, 3, 5, 5, 5]
    """

    for _____:

        yield from [_____]
```

2. Complete the implementation of `iter_link`, which takes in a linked list and returns a generator which will iterate over the values of the linked list in order. Your function should support deep linked lists.

```
def iter_link(lnk):
    """
    Yield the values of a linked list in order; your function
    should support deep linked lists.
    >>> lst1 = Link(1, Link(2, Link(3, Link(4))))
    >>> list(iter_link(lst1))
    [1, 2, 3, 4]
    >>> lst2 = Link(1, Link(Link(2, Link(3)), Link(4, Link(5))))
    >>> print(lst2)
    <1 <2 3> 4 5>
    >>> iter_lst2 = iter_link(lst2)
    >>> next(iter_lst2)
    1
    >>> next(iter_lst2)
    2
    >>> next(iter_lst2)
    3
    >>> next(iter_lst2)
    4
    """
    if lnk is not Link.empty:
        if type(_____) is Link:
            _____
        else:
            _____
            _____
```